

# MATERIAL SAFETY DATA SHEET

## SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** COLOURGUARD, MACHINE COLOURGUARD.

**Company:** Inhouse Management Pty Ltd. 286 Victoria Road Malaga, Western Australia 6090. Telephone (08) 9248 4007. Fax: (08) 9248 4015. Emergency Contact: (08) 9248 4007

**Other Names:** N/A

**Recommended Use:** Staining of timber.

## SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA NOT DANGEROUS ACCORDING TO THE CRITERIA OF THE ADG CODE**

**Symbols:** Xn Harmful

**Risk Phrases:**

R65 -Harmful: May cause lung damage if swallowed

R66 -Repeated exposure may cause skin dryness or cracking

**Safety Phrases:**

S2 Keep out of the reach of children

S23 Do not breath vapour

S24 Avoid contact with skin

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show container or label.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### INGREDIENTS

<u>Chemical Entity</u>	<u>CAS Number</u>	<u>Proportion</u>
Kerosene (petroleum), hydrosulphurised	64742-8 1-0	90%
Alkyd resin		<10%
Iron Oxide	1309-37-1	<10%

## SECTION 4 FIRST AID MEASURES

### FIRST AID TREATMENT

**Swallowed:** If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

**Eyes:** If in eyes, hold eyes open, flood with water for at least 15 minutes. If redness, burning, blurred vision, or swelling persist transport to nearest medical facility for additional treatment.

**Skin:** If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available.

**Inhaled:** Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing

**First Aid facilities:** Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers.

**Advice to Doctor:** Treat symptomatically.

**Additional Information:** None available.

## SECTION 5 FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Foam, water spray or fog, dry chemical powder. Do not use water in a jet.

**Hazards from combustion products:** Will float and can be reignited on surface water. Vapour is heavier than air, can spread along ground and distant ignition is possible.

**Precautions for Fire Fighters and Special Protective Equipment:** Wear full protective clothing and self-contained breathing apparatus.

**Additional Information:** Hazchem code -Not applicable

## SECTION 6 ACCIDENTAL RELEASE MEASURES

Observe all local and national regulations

**Spills and Disposal:** Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Remove all sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.

**Methods and Materials for Containment and Clean Up Procedures:** For small spills (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

## **SECTION 7 HANDLING AND STORAGE**

Precautions for Safe Handling and Storage: Avoid breathing of or contact with material. Use in well ventilated areas. Wash thoroughly after handling. Avoid contact with skin and eyes and clothing. Handle open containers in well ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Do not empty into drains. Do not eat, drink or smoke in contaminated areas. Before eating, drinking or smoking, remove contaminated clothing and wash hands. Do not store near strong oxidants.

Dispensing: Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment.

Flammability: Combustible

## **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure Standards: In the absence of occupational exposure standards for this product, it is recommended that the following are adopted. 350mg/m<sup>3</sup> TWA (8hr)

Personal Protective Equipment: Respiratory Protection: If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter and select a filter for organic gases and vapours (boiling point > 65 Deg C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.

Hand Protection: Use solvent resistant gloves. Nitrile for longer term protection or PVC and neoprene for incidental splashes.

Eye Protection: Wear safety Goggles.

Protective Clothing: Use chemical resistant glove/gauntlets, boots and apron. Skin protection not ordinarily required beyond standard issue work clothes.

Engineering Controls: Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists. Keep containers closed when not in use.

## **SECTION 9 IDENTIFICATION**

### **PHYSICAL DESCRIPTION / CHEMICAL PROPERTIES**

Appearance: Colourless liquid

Odour: Paraffinic

pH: N/A

Vapour Pressure (kPa @ 20°C): Data not available

Vapour Density (air = 1): >1

Boiling Point (°C): Typical 195 -250

Freezing/Melting Point (°C): Data not available

Solubility in Water: Negligable

Specific Gravity (g/ml @ 15°C): 0.80 -0.83

Flashpoint (°C): Typical 75 (CC)

Flammability Limits (%): 0.6 -7.0

Auto Ignition Temperature (°C): > 200

Percent Volatiles: 100%

## **SECTION 10 STABILITY AND REACTIVITY**

Chemical Stability: Stable under normal conditions of use.

Conditions to Avoid: Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials: Strong oxidising agents.

Hazardous Decomposition Products: Thermal decomposition is highly dependant on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## **SECTION 11 TOXOCOLOGICAL INFORMATION**

### **HEALTH EFFECTS**

Acute:

Swallowed: Expected to be of low toxicity: Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis. Expected to be non-irritating to eyes

Skin: Prolonged contact may cause defatting of skin which can lead to dermatitis.

Inhaled: Inhalation of vapours or mists may cause irritation to the respiratory system.

Chronic:

Central nervous system: repeated exposure affects the nervous system

**SECTION 12 ECOLOGICAL INFORMATION**

**Ecotoxicity:**

Fish: Harmful 10< LC/EC/IC50<= 100mg/l

Aquatic invertebrates: Low toxicity: LC/EC/IC50> 100mg/l

Algae: Harmful 10< LC/EC/IC50<= 100mg/l

Microorganisms: Expected to be Harmful 10< LC/EC/IC50<= 100mg/l

Mobility: Floats on water. Adsorbs to soil and has low mobility

Persistence/degradability: Readily Biodegradable. Degrades rapidly in air by photo-chemical means.

Bioaccumulation: Has the potential to bioaccumulate.

**SECTION 13 DISPOSAL CONSIDERATIONS**

Disposal Methods: Ensure waste disposal conforms to local waste disposal regulations.

**SECTION 14 TRANSPORT INFORMATION**

UN		Proper Shipping Name:	N/A
Number:	N/A	Subsidiary Risk:	None allocated
Class:	N/A	Hazchem Code:	N/A
Packing			
Group:	N/A		
Special			
Precautions			
for User:	None		

**SECTION 15 REGULATORY INFORMATION**

Poisons Schedule: 5

AICS: Listed

Dangerous Goods Initial Emergency Response Guide (SAAISNZ HB76: 1997): None

**SECTION 16 OTHER INFORMATION**

Further Information may be obtained by contacting Inhouse Management Pty Ltd (T.as) TIMBACHEM on (08)9248 4007.

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the Company's responsibilities surrounding the supply of this product, undertaken in good faith.